

FEATURES & SPECIFICATIONS

INTENDED USE

A wrap around fluorescent fixture designed for parking garages, school corridors or any application where high abuse or vandalism could occur.

Construction

Back plate is die formed of 16 gauge steel. Lens attached to back plate with tamper resistant stainless steel screws.

Diffuser

Diffuser is made of injection molded UV stabilized 100% clear, polycarbonate with an internal prismatic pattern.

Mounting

Units may be surface or wall mounted.



Electrical

Unless otherwise specified, ballasts are rapid start, class "P" thermally protected, H.P.F., CBM-ETL. Optional ballasts available include: energy saving (ESB), electronic (ELB), dimming (DIM), low temperature (CW). Standard voltage on all fixtures is 120V 60Hz AC, or as specified. Sufficient knockouts are provided on the back for all connections and through wiring.

ORDERING INFORMATION

Example: CV800F40W4000LDMV40KWH

CV800	F40W4000L	DMV	40K	WH
Series	Wattage and Lumen	Driver	Color Temperature	Finish
CV800	F40W4000L 40 System Watts, 4000 Delivered Lumens	DMV 0-10V Dimming * Field installed-Dimming Wire DMVFID 0-10V Dimming * Factory installed-Dimming Wire	30K 3000K 35K 3500K 40K 4000K 50K 5000K	WH WHITE
				Options [1]
				WP 6ft. 3 wire 18 gauge whip WP10 6ft. 4 wire 18 gauge whip EM Emergency ballast

