

ECL SERIES

Eclipse Surface Mount



X1LED Eclipse is the ideal light for many residential applications like kitchens and utility rooms and many other commercial applications. The X1LED eclipse fixtures utilize efficient LED T8 lamps that provide high lumen output with efficient energy savings. Since they don't require any ballast or driver the only component that will ever need changing is the LED T8 lamp. The lamps are warranted for five years. Unlike other Surface Mount fixtures that utilize LED arrays and drivers these fixtures have the flexibility to change wattage, lumens, and color temperature simply by changing the lamps without the need to call a licensed electrician.

LAMP

2 or 4 lamp positions

CONSTRUCTION

Designed especially for the T8 lamp, electronic ballast and today's interiors, this low profile softly rounded silhouette will eclipse the competition. The Eclipse is 2" shallower than the Puff. All colors are available for immediate shipment. Packed in one carton.

SIZE W x L x H in inches (mm)

- 2 Lamp: 9.5W x 25.75L x 4.5Dp (2ft.)
- 2 Lamp: 9.5W x 51.25L x 4.5Dp (4ft.)
- 4 Lamp: 16.5W x 25.75L x 5.0Dp (2ft.)
- 4 Lamp: 16.5W x 51.25L x 5.0Dp (4ft.)

X1 LED

The most economical, practical and user friendly series of LED fixtures with the energy savings, quality of light, long life and hassle-free maintenance. X1 LED fixtures are UL Listed with the latest LED T8 Bypass lamps. Fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required) and have flexibility to change wattage and color temperature any time. Fixture performance will evolve over time with the evolution of the T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture, X1 LED solves that by utilizing a self contained LED lamp that fits into fixture just like a fluorescent lamp.

Lamp Specifications:

Our T8 LED lamps are available in 2 or 4 ft sizes in different wattage, lumens and color temperature options. See lamp options and specs at www.texasfluorescents.com/X1LEDLamps.

- 50,000 Hour Life with 5 Year Warranty
- Beam Angle 140 Degree
- Aluminum Base and Aluminum Housing with Glass Cover
- Operating Temperature: - 20C to 50C
- Color Temperature: 3500K, 4000K, 5000K
- G13 Pins (Same as Fluorescent Linear T8 Bipin)
- AC100 – 277V without Ballast
- Single Ended or Double Ended Power (If not specified use X1 Single Ended Power)

Optional Dimming Options:

The 4 FT lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps. So more than 2 lamps require multiple external drivers. See dimming options and specs at www.texasfluorescents.com/X1LEDdimming.

Emergency Options:

The standard X1 LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it. See emergency options and specs at www.texasfluorescents.com/X1LEDemergency.

| ITEM NO. | DESCRIPTION |
|--|--|
| ECLMW217X1WHLN15W40K (AL, BM, IM, SI, WM) | 9x24 inches 3400 Lumen w/2x15W LED T8 4000K Lamps Included |
| ECLMW232X1WHLN18W40K (AL, BM, IM, SI, WM) | 9x48 inches 4200 Lumen w/2x18W LED T8 4000K Lamps Included |
| ECLMW417X1WHLN15W40K (AL, BM, IM, SI, WM) | 17x24 inches 6800 Lumen w/4x15W LED T8 4000K Lamps Included |
| ECLMW432X1WHLN18W40K (AL, BM, IM, SI, WM) | 17x48 inches 8400 Lumen w/4x18W LED T8 4000K Lamps Included |

Change 40 to 35 or 50 for different Kelvin. Change Lamp Wattage to 13W on 2FT or 15W on 4FT



| |
|-----------------|
| Catalog Number: |
| Notes: |