

Smart Sense H2L Series

H2L High Bay Workhorse

FEATURES & SPECIFICATIONS

INTENDED USE

The H2L series is the workhorse of our high bay fluorescent series, designed especially for high light output. The fixtures uses premium mirrored or white reflectors for high efficiency lighting. A sturdy/ durable fixture body with superior appearance and appeal, suitable for commercial, retail and industrial applications. Mounts easily with chain or cable kit. The Smart Sense version incorporates an integral Sensor Switch Occupancy Sensor in the reflector and protected by an optional wire guard. No need for an external sensor with this full functioning Occupancy Sensor. See Sensor Switch spec sheet below.

SIZE W x L x H in inches (mm)

7W x 48L x 3Dp

CONSTRUCTION

Body and ends are die blanked, pierced and formed of 20 gauge cold rolled prime steel for rigidity and uniformity. Forming of the housing has been engineered to provide added strength along its entire length.

LAMP

1 or 2 Lamp Positions; T5 or T8.

MATERIALS & FEATURES

Baked white enamel code gage steel Premium full specular mirrored reflector Multiple KOs and access plate.



Integral Sensor Switch
Occupancy Sensor

MOUNTING

4 Point chain mount. For other options, consult factory.

LISTING / CERTIFICATIONS

Fixture & Ballast: UL Listed

TYPICAL OPTIONS AND ACCESSORIES

Emergency ballasts, Cord sets, whips, occupancy sensors Hanging kits, Wire guards. Contact factory for additional options.

ORDERING INFORMATION

Example: **H2L254M23MV**

H2L	2	54	M23	MV
Series		Lamp Type	Reflector	Ballast & Voltage [1]
H2L High Bay Workhorse SSH2L Smart Sense High Bay		54 46 in. T5 32 48 in. T8	M23 Mirrored wide distribution W13 Enhanced white Aluminum W12 Enhanced white Reflector w/ integral sensor and air vents.	S Residential 120V Ballast MV Electronic, Multivolt (120-277) X1 No Ballast Wired for Single ended LED lamps X2 No Ballast Wired for Double ended lamps Electronic 120V X No Ballast
Lamp Count		Options [1]		
1 2 (Lamps not included)		CS 5-15P 120V 8ft. Cord & Plug CS12 L7-15P 277V 8ft. Cord & Plug CS08 8ft. Cord, No Plug WP 6 ft. 3 wire, Whip WP10 6ft. 4 wire, Whip EM Emergency ballast, 500 lumens EM14 Emergency ballast, 1400 lumens LN15W30 Single ended 15W 1800 Lumen 3500K* included LN15W30 Single ended 18W 2100 Lumen 3500K* included		
Accessories				
Order as Seperate Part Number				
H2LLEN	Clear Lens. Mounts .25" off fixture.			
HC101	Chain kit, Includes: 6 S Hooks and 20ft. chain			
HC202	Tong hangers, End Mount (Pair)			
HC203	Tong hangers, Side Mount (Pair)			
7H6L	Single Point hanger adapter			
H2L2WG	2 Lamp Wire Guard			

Consult for cord, hanging and occupancy sensor options.

*Change 30 to 40 or 50 for 4000K or 5000K

Catalog Number:
Notes: