

# Spill Ring Series

## Close-to-Ceiling

### HOTCD Series

#### FEATURES & SPECIFICATIONS

Stylish ceiling luminaire in either satin nickel or bronze is available in multiple sizes to meet a variety of applications. Matching wall, bath and linear versions make this series ideal for multi-family or hospitality applications.

#### MOUNTING

Back plate provided with adequate knockouts and mounting holes for either wall or ceiling installation.

#### CONSTRUCTION

All metal parts are die-formed from heavy gauge cold roll steel.

#### DIFFUSER

Opal acrylic shade.

#### WIRING

Choice of GU Lamps, Quad Lamps or LED.



#### LISTING

Fixtures conform to Underwriters' Laboratories standards for production and are carefully tested prior to packing. UL damp Listed. Consult for Energy Star. LED versions are ETL listed.

#### WARRANTY

LED components have 5 year limited warranty.

#### COMPACT FLUORESCENT

Item Number	Dimensions (L x W x H)	Lamping
HOTCD118GUSN	10" x 10" x 4.25"	1-18W GU MAX
HOTCD118SSN	10" x 10" x 4.25"	1-18W Quad 4 Pin
HOTCD126GUSN	12" x 12" x 4.25"	1-26W GU MAX
HOTCD218GUSN	14" x 14" x 4.25"	2-18W GU MAX
HOTCD218SSN	14" x 14" x 4.25"	2-18W Quad 4 Pin
HOTCD226GUSN	17.75" x 17.75" x 4.25"	2-26W GU MAX
HOTCD226SSN	17.75" x 17.75" x 4.25"	2-26W Quad 4 Pin
HOTCDO232SSN	32.3" x 18.1" x 4.25"	2-FC12T9 (32W CIRC)

Lamps Now Sold Separately. Consult Factory for emergency option and other lamping options.

#### LED

Item Numbers	Input Voltage A1	Watts	Lumens	Finish	Color	Dimensions
HOTCD12L17W1200LD120SN40K**	120V Triac dimming	17	1200	SATIN NICKEL	4000	12"Dia x 4.2"H
HOTCD12L18W1400LMVSN40K**	120V-277V	18	1400	SATIN NICKEL	4000	12"Dia x 4.2"H
HOTCD14L23W1600LMVSN40K**	120V-277V	23	1600	SATIN NICKEL	4000	14.5"Dia x 4.6"H
HOTCD16L28W2050LMVSN40K**	120V-277V	28	2050	SATIN NICKEL	4000	16"Dia x 4.9"H
HOTCD18L33W2400LMVSN40K**	120V-277V	33	2400	SATIN NICKEL	4000	17.8"Dia x 4.9"H
Item Numbers	Input Voltage A1	Watts	Lumens	Finish	Color	Dimensions
HOTCDOLF28W2050LMVSN40K	120V-277V	28	2050	SATIN NICKEL	4000	32.3"Lx18.1"Wx4.25"H
HOTCDOLR48W4000LMVSN40K	120V-277V	48	4000	SATIN NICKEL	4000	32.3"Lx18.1"Wx4.25"H

Change 40K to 30K for 3000K color temperature.

\* LED Driver: 120V dimming type or 120V ~ 277V, constant current type

\* Certification: ETL / cETL

\* LED: Nichia or LG, 50,000 hours rating

\* LED Color Temperature: 3000K or 4000K

\* LED CRI: 80 min on 4100K and 3000K

\* Warranty - 5 years



Texas Fluorescents

2055 Luna Rd. Suite 142 Carrollton, TX 75006

Phone: 972-247-3171 Fax: 972-247-0200

www.texasfluorescents.com email: sales@texasfluorescents.com

Catalog Number:

Notes: