



T E X A S

F L U O R E S C E N T S

LED Flood Light

This compact, yet durable die-cast aluminum floodlight provides a flood of light from a single LED diode. Lighting Facts approved to provide 1500 lumens and 50,000 hours of life using 20 watts. It is an ideal replacement for a 50W HID. Die cast swivel are 1/2" NPS makes mounting simple to a standard junction box. Integrated heat fins, white reflector and tempered glass lens ensures optimum performance and suitable for wet location. Available in bronze or white finishes. Ideal applications for security, building facades, displays, uplighting and signs. Good for lower level lighting in storage areas and commercial sites.



FEATURES AND CHARACTERISTICS

- Sturdy aluminum die cast housing and face grame
- Durable polyester powder coat finish
- Tempered glass lens
- Integrated heat fins for optimized heat dissipation
- White Reflector
- 1/2" NPS die casting swivel arm
- LED: Citizen CLL032-1208 with LM80 or Equivalent
- System Power Consumption: 30W
- Delivered Lumens: 2700 Lumens, Lighting Facts Approved
- Input Voltage: 120-277Vac 50/60 HZ
- 4000K Color Temperature
- Minimum starting temperature -22 Degrees F
- No Dimmable
- UL/CUL listed for Wet Locations
- Package 1 Piece per box, 12 Pieces Master Carton
- 5 Year Limited Warranty

ORDERING INFORMATION

Item No.	Description	Size
LFS57L30W2700LMV40KBZ	LED FLOOD SQ 30W 2700L MV 40K BZ	7.75"W x 5.75"H x 6.5"Ext
LFS57L30W2700LMV40KWH	LED FLOOD SQ 30W 2700L MV 40K WH	7.75"W x 5.75"H x 6.5"Ext

Catalog Number:
Notes: