

RCR and RCS series

Ultra Thin Faux Downlight

Specifications

Now Performance of a recessed downlight in an extremely low profile (less than one inch deep) surface mount LED fixture. Choose either a round or square silhouette in two sizes and two finishes, white and brushed nickel with a special regressed lens to provide even, comfortable illumination from these edge-lit fixtures. Now enjoy the most consistent, low wattage general lighting from a sleek, fresh appearance. Fixture with LED driver mounts easily to a snap in brackets that fits into a standard junction box. Wet location for indoor and outdoor use. 120V only. Dims to 10% with standard dimming.

Mounting

Surface mounts to existing Junction-box or new construction with two screws.

LED Engine

Slim closet to ceiling LED arrays providing 10watts with 660 lumens and 15 watts with 1000 lumens at 3000K color temperature.

Dimming

RCR and RCS Series dims to 10% with standard dimmers*

* Triac Based (forward phase control or leading edge dimmers).

Note: Specifications subject to change without notice

Dimensions

RCR5L - 5.5" D x 0.625" H

RCR7L - 7" D x 0.625" H

RCS5L - 6.28" L x 0.625" H

RCS7L - 8" L x 0.625" H



Listing

ETL Indoor or Outdoor.

Suitable for Wet Location

Warranty

5 Year Limited Warranty

Finish

White, Brushed Nickel



Example: **RCR5L10W30KWH**

Ordering Information

Item No.	Description	Dimensions
RCR5L10W30KWH (or BN)	Ultra Thin Round LED 5" (5.5" OD) White (or Brushed Nickel), 10W 660 lumens, 3000K, 120V, Dimmable Driver, Surface Mount, Suitable Indoor/Outdoor	5.5" D x 0.625" H
RCR7L15W30KWH (or BN)	Ultra Thin Round LED 7" (7" OD) White (or Brushed Nickel), 15W 1000 lumens, 3000K, 120V, Dimmable Driver, Surface Mount, Suitable Indoor/Outdoor	7" D x 0.625" H
RCS5L10W30KWH (or BN)	Ultra Thin Square LED 6.28" White (or Brushed Nickel), 10W 660 lumens, 3000K, 120V, Dimmable Driver, Surface Mount, Suitable Indoor/Outdoor	6.28" L x 0.625" H
RCS7L15W30KWH (or BN)	Ultra Thin Square LED 8" White (or Brushed Nickel), 15W 1000 lumens, 3000K, 120V, Dimmable Driver, Surface Mount, Suitable Indoor/Outdoor	8" L x 0.625" H