



T E X A S

F L U O R E S C E N T S

# SCB 1x4

LED Architectural Direct/Indirect Luminaire

## FEATURES & SPECIFICATIONS

### INTENDED USE

This sleek, low profile, direct/indirect fixture provides a soft, smooth, low glare, ambient light perfect for today's commercial buildings. This unique, squared lens, combined with our high reflectance, post powder paint, matte finish, ensure a highly efficient, superior quality lighting fixture.



### FEATURES

- Recessed or surface mounted
- Post painted in matte white finish with 92% reflectance
- Acrylic frosted diffuser with 90% light transmission
- Formed and welded in 24 gauge steel
- Direct/indirect lighting
- Easy removal of diffuser without any tools
- Volumetric low cost center lens
- LEDs life >60,000 hours
- >80 CRI
- 5 Years Warranty



Frosted Side Lens



Perforated Side Lens

### SIZE W x L x H in inches

**1x4** 12.00"W x 48.00"L x 3.34"D

**2x2** 24.00"W x 24.00"L x 3.36"D

**2x4** 24.00"W x 48.00"L x 3.26"D

## 1X4 ORDERING INFORMATION

Example: UCLL14LF32W3450LDMV40K

SCB	14L	F32W3450L	DMV	40K
Series	Size	Wattage / Lumen	Driver	Color Temperature
SCB Architectural Direct/Indirect Luminaire	14L	<b>F15Y 1650N</b> 15 System Watts, 1650 Delivered Lumens <b>F22Y 2700N</b> 30 System Watts, 4000 Delivered Lumens <b>F35Y 3900N</b> 35 System Watts, 4600 Delivered Lumens <b>F40Y 5100N</b> 40 System Watts, 5100 Delivered Lumens <b>F48Y 6000N</b> 48 System Watts, 6000 Delivered Lumens <b>F57Y 6000N</b> 57 System Watts, 7000 Delivered Lumens	<b>DMV</b> 0-10V Dimming *Field installed-Dimming Wire <b>DMVFID</b> 0-10V Dimming *Factory installed-Dimming Wire	<b>52M'</b> 3000K <b>57M'</b> 3500K <b>40K</b> 4000K <b>50K</b> 5000K

\* Consult FACTORY for more options

Catalog Number:
Notes:



T E X A S

F L U O R E S C E N T S

# SCB 2x2

LED Architectural Direct/Indirect Luminaire

## 2x2 ORDERING INFORMATION

SCB	22L	F18W2100L	DMV	40K
<b>Series</b>	<b>Size</b>	<b>Wattage / Lumen</b>	<b>Driver</b>	<b>Color Temperature</b>
SCB Architectural Direct/Indirect Luminaire	22L	<b>F18Y 1800N</b> 18 System Watts, 1780 Delivered Lumens <b>F20Y 2200N</b> 20 System Watts, 2155 Delivered Lumens <b>F24Y 2600N</b> 24 System Watts, 2565 Delivered Lumens <b>F30Y 3000N</b> 30 System Watts, 3065 Delivered Lumens	<b>DMV</b> 0-10V Dimming *Field installed-Dimming Wire <b>DMVFD</b> 0-10V Dimming *Factory installed-Dimming Wire	<b>52M'</b> 3000K <b>57M'</b> 3500K <b>40K</b> 4000K <b>50K</b> 5000K

## 2x4 ORDERING INFORMATION

SCB	24L	F18W2100L	DMV	40K
<b>Series</b>	<b>Size</b>	<b>Wattage / Lumen</b>	<b>Driver</b>	<b>Color Temperature</b>
SCB Architectural Direct/Indirect Luminaire	24L	<b>F30W3500L</b> 30 System Watts, 3480 Delivered Lumens <b>F35W3900L</b> 35 System Watts, 3900 Delivered Lumens <b>F40W4500L</b> 40 System Watts, 4500 Delivered Lumens <b>F48W5200L</b> 48 System Watts, 5200 Delivered Lumens <b>F57W6100L</b> 40 System Watts, 5200 Delivered Lumens  48 System Watts, 6200 Delivered Lumens  57 System Watts, 7200 Delivered Lumens	<b>DMV</b> 0-10V Dimming *Field installed-Dimming Wire <b>DMVFD</b> 0-10V Dimming *Factory installed-Dimming Wire	<b>52M'</b> 3000K <b>57M'</b> 3500K <b>40K</b> 4000K <b>50K</b> 5000K

\* Consult FACTORY for more options

Catalog Number:

Notes: